

dolin

8048.01 - 8048.09



binder
curtain

omschrijving
licht gestructureerde melange

samenstelling
100% brandvertragend polyester

breedte
± 140 cm, ± 55 inches

gewicht
± 407 gr/m¹, ± 13 oz/yd¹ fabrics

geluidsabsorptie
ISO 354
alphaw 0.85 (pleated)

visueel & thermisch comfort
EN 410/EN 14501

brandwerendheid
EN 13773, class 1
BS 5867-2, type C
NF P 92/503-507, M1
DIN 4102, B1
UNI VF 8456-8457, classe 1
IMO 2010 FTP part 7
NFPA 701
CAN ULC S109

wrijftechtheid
ISO 105-X12
nat 4-5 / droog 4-5 (schaal 1-5)
AATCC 8
nat 5 / droog 5 (schaal 1-5)

lichtechtheid
ISO 105-B02
6 (schaal 1-8)
AATCC 16.3: 60 hrs
5 (schaal 1-5)

naadschuifweerstand
ISO 13936-2
ketting 5.5 mm / inslag 4.7 mm
ASTM D434
ketting 32 lbs / inslag 30 lbs

onderhoud



krimp: ketting -2% / inslag -1%



krimp: ketting -2.8% / inslag -2%



STANDARD
100
S07-0023
Hohenstein HTTI



dolin


8048.01 - 8048.09



8048.01




8048.02




8048.03




8048.04




8048.05



8048.06



8048.07



8048.08



8048.09