

dolin

8048.01 - 8048.09



binder
curtain

description
light textured blend

composition
100% flame retardant polyester

width
± 55 inches, ± 140 cm

weight
± 13 oz/yd¹, ± 407 gr/m¹ fabrics

sound absorption
ISO 354
alphaw 0.85 (pleated)

visual & thermal comfort
EN 410/EN 14501

flame retardancy
EN 13773, class 1
BS 5867-2, type C
NF P 92/503-507, M1
DIN 4102, B1
UNI VF 8456-8457, classe 1
IMO 2010 FTP part 7
NFPA 701
CAN ULC S109

colorfastness to crocking
ISO 105-X12
wet 4-5 / dry 4-5 (scale 1-5)
AATCC 8
wet 5 / dry 5 (scale 1-5)

colorfastness to light
ISO 105-B02
6 (scale 1-8)
AATCC 16.3: 60 hrs
5 (scale 1-5)

seam slippage
ISO 13936-2
warp 5.5 mm / weft 4.7 mm
ASTM D434
warp 32 lbs / weft 30 lbs

care



shrinkage: warp -2% / weft -1%



shrinkage: warp -2.8% / weft -2%



STANDARD
100
S07-0023
Hohenstein HTTI



Text below the logo, likely identifying the certifying institution.

dolin


8048.01 - 8048.09



8048.01




8048.02




8048.03




8048.04




8048.05



8048.06



8048.07



8048.08



8048.09