

faray

8058.01 - 8058.18



binder
curtain

description
ton sur ton dessin of "swirling" lines in the length

composition
100% flame retardant polyester

width
± 140 cm, ± 55 inches

weight
± 312 gr/m¹, ± 10 oz/yd¹ fabrics

visual & thermal comfort
EN 410/EN 14501

flame retardancy
EN 13773, class 1
BS 5867-2, type C
NF P 92/503-507, M1
DIN 4102, B1
UNI VF 8456-8457, classe 1
IMO 2010 FTP part 7
NFPA 701
CAN ULC S109

colorfastness to crocking
ISO 105-X12
wet 4-5 / dry 4-5 (scale 1-5)
AATCC 8
wet 5 / dry 5 (scale 1-5)

colorfastness to light

ISO 105-B02

6-7 (scale 1-8)

AATCC 16.3: 60 hours

5 (scale 1-5)

seam slippage

ASTM D434

warp 40.5 lbs / weft 58 lbs

care



shrinkage: warp: -0.2% / weft: -0.2%



shrinkage: warp: -0.9% / weft: -0.6%



STANDARD
100
S07-0023
Hohenstein HTTI



Text below the logo, likely identifying the certifying institution.

faray

8058.01 - 8058.18



8058.01



8058.02




8058.03



8058.04



8058.05



8058.06



8058.07



8058.08




8058.09




8058.10




8058.11



8058.12




8058.13




8058.14




8058.15



8058.16



8058.17



8058.18