

# faray

8058.01 - 8058.18



binder  
curtain

description  
ton sur ton dessin of "swirling" lines in the length

composition  
100% flame retardant polyester

width  
± 55 inches, ± 140 cm

weight  
± 10 oz/yd<sup>1</sup>, ± 312 gr/m<sup>1</sup> fabrics

visual & thermal comfort  
EN 410/EN 14501

flame retardancy  
EN 13773, class 1  
BS 5867-2, type C  
NF P 92/503-507, M1  
DIN 4102, B1  
UNI VF 8456-8457, classe 1  
IMO 2010 FTP part 7  
NFPA 701  
CAN ULC S109

colorfastness to crocking  
ISO 105-X12  
wet 4-5 / dry 4-5 (scale 1-5)  
AATCC 8  
wet 5 / dry 5 (scale 1-5)

colorfastness to light

ISO 105-B02

6-7 (scale 1-8)

AATCC 16.3: 60 hours

5 (scale 1-5)

seam slippage

ASTM D434

warp 40.5 lbs / weft 58 lbs

care



shrinkage: warp: -0.2% / weft: -0.2%



shrinkage: warp: -0.9% / weft: -0.6%



STANDARD  
100  
S07-0023  
Hohenstein HTTI



# faray

8058.01 - 8058.18

---



8058.01



8058.02




8058.03



8058.04



8058.05



8058.06



8058.07




8058.08




8058.09




8058.10




8058.11



8058.12




8058.13




8058.14




8058.15



8058.16



8058.17



8058.18