

faray

8058.01 - 8058.18



binder
curtain

描述

ton sur ton dessin of “swirling” lines in the length

组成

100% 阻燃聚酯纤维

宽度

± 140 cm, ± 55 inches

重量

± 312 gr/m², ± 10 oz/yd² fabrics

温度及视觉舒适度

EN 410/EN 14501

阻燃

EN 13773, class 1

BS 5867-2, type C

NF P 92/503-507, M1

DIN 4102, B1

UNI VF 8456-8457, classe 1

IMO 2010 FTP part 7

NFPA 701

CAN ULC S109

耐擦拭

ISO 105—X12

湿 4-5 / 干 4-5 (由 1—5)

AATCC 8

湿 5 / 干 5 (由 1—5)

耐褪色

ISO 105—B02

6-7 (由 1-8)

AATCC 16,3: 60 hours

5 (由 1-5)

耐滑缝

ASTM D434

warp 40,5 lbs / weft 58 lbs



收缩□ : 纵向收缩比: -0.2% / 横向收缩比: -0.2%



收缩□ : 纵向收缩比: -0.9% / 横向收缩比: -0.6%



STANDARD
100
S07-0023
Hohenstein HTTI



Text below the logo, likely identifying the institution or certification body.

faray

8058.01 - 8058.18



8058.01



8058.02




8058.03



8058.04



8058.05



8058.06



8058.07



8058.08




8058.09




8058.10




8058.11



8058.12




8058.13




8058.14




8058.15



8058.16



8058.17



8058.18