

# bray+print

8065.01



binder

**curtain+print**

description

**floor-to-ceiling curtain+print black out with an non-directional weave structure**

composition

**100% flame retardant polyester acrylic coating**

width

**± 280 cm, ± 110 inches**

printable width

**± 270 cm, ± 106 inches**

weight

**± 1075 gr/m<sup>1</sup>, ± 35 oz/yd<sup>1</sup> fabrics**

visual & thermal comfort

**EN 410/EN 14501**

**AATCC 148**

flame retardancy

**EN 13773, class 1**

**BS 5867-2, type B**

**DIN 4102, B1**

**UNI VF 8456-8457, classe 1**

**NFPA 701**

**CAN/ULC S109**

**IMO 2010 FTP part 7**

colorfastness to crocking

**ISO 105-X12**

wet 4-5 / dry 4-5 (scale 1-5)

**AATCC 8**

wet 5 / dry 5 (scale 1-5)

colorfastness to light

**ISO 105-B02**

5 (scale 1-8)

**AATCC 16.3: 60 hours**

2.5 (scale 1-5)

seam slippage

**ASTM D434**

warp 44 lbs / weft 49.5 lbs

additional information

**This image is not part of our collection, but should be regarded as an example.**

care



**shrinkage: warp -0.9% / weft -0.6%**



**shrinkage: warp -1.5% / weft -1.2%**



Hochschule Rhein-Waal  
47699 Krefeld

# bray+print

8065.01

---



8065.01