


noss

7058.01 - 7058.24



binder

upholstery

omschrijving

geweven chenille, melange in zachte kleuren

samenstelling

100% brandvertragend polyester

breedte

± 140 cm, ± 55 inches

gewicht

± 904 gr/m¹, ± 29 oz/yd¹ fabrics

brandwerendheid

EN 1021/ 1-2

BS 5852, crib 5

NF P 92 / 503 - 507, M1

DIN 4102, B1

UNI 9175, classe 1 IM

Cal TB 117

NFPA 260, class 1

IMO 2010 FTP part 8

slijtvastheid

ISO 12947-2

70.000 rubs martindale

ASTM D4157

90.000 double rubs wyzenbeek

pilling

ISO 12945-2

4 (schaal 1-5)

ASTM D3511

5 (schaal 1-5)

wrijfechtheid

ISO 105-X12

nat 4 - 5 / droog 4 - 5 (schaal 1-5)

AATCC 8

nat 5 / droog 5 (schaal 1-5)

lichtechtheid

ISO 105-B02

6 - 7 (schaal 1-8)

AATCC 16.3: 40 hours

5 (schaal 1-5)

naadschuifweerstand

ISO 13936 - 2

ketting 3.3 mm / inslag 3 mm

ASTM D4034

ketting 77 lbs / inslag 91 lbs

treksterkte

ASTM D5034

warp 524 lbs / weft 337 lbs

onderhoud



krimp: ketting -1.5% / inslag -1.7%



krimp: ketting -1.6% / inslag -3%



STANDARD
100

S07-0023
Hohenstein HTTI

noss

7058.01 - 7058.24



7058.01



7058.02



7058.03



7058.04



7058.05



7058.06




7058.07



7058.08




7058.09



7058.10



7058.11



7058.12



7058.13



7058.14



7058.15



7058.16



7058.17




7058.18



7058.19



7058.20



7058.21



7058.22



7058.23



7058.24