

# creek

7053.01 - 7053.22



## binder

upholstery

vinyl

## 描述

三色不规则亚麻外观

## 组成

发泡PVC,加棉或涤底

## 宽度

± 137-140 cm, ± 54-55 inches

## 重量

底层: ± 110 gr/m<sup>2</sup>, ± 5 oz/yd<sup>1</sup>

涂层: ± 690 gr/m<sup>2</sup>, ± 31 oz/yd<sup>1</sup>

## 厚度

1,1 mm, 0,04 inches

## 阻燃

EN 1021/1—2

BS 5852, crib 5

NF P 92/503 — 507, M2

NF D60—013 (AM 18)

DIN 4102, B2

UNI 9175, classe 1 IM

Cal TB 117

NFPA 260, class 1

IMO 2010 FTP part 8

## 耐磨性

ISO 12947—2

> 300,000 rubs martindale

ASTM D4157

100,000 double rubs wyzenbeek

## 耐擦拭

ISO 105—X12

wet 5 / dry 5 (scale 1—5)

AATCC 8

wet 5 / dry 5 (scale 1—5)

## 耐褪色

ISO 105—B02

7 (scale 1—8)

ASTM D4329: 150 hours

4 (scale 1—5)

## 耐血液，尿液，汗液和皮肤脂肪

EN 12720

5 (scale 1—5)

## 屈伸强度

ISO 1421

length 470 N / width 313 N

ASTM D2261

length 7.3 lbs / width 9.2 lbs

## 灵活性

ISO 7854

400,000 cycles

## 涂层粘结力

ASTM D751

length 8.3 lbf / width 5.2 lbf




**vinyl**   
COMMITTED TO  
SUSTAINABLE DEVELOPMENT


# creek

7053.01 - 7053.22


---




7053.01




7053.02




7053.03




7053.04




7053.05




7053.06




7053.07




7053.08




7053.09



7053.10




7053.11




7053.12




7053.13




7053.14




7053.15




7053.16




7053.17




7053.18




7053.19



7053.20



7053.21



7053.22