

# dikson

7063.01 - 7063.14



binder

**upholstery**

descripción

**tapicería de mezcla sofisticada de hilos  
suaves de chenilla**

composición

**> 40% recycled polyester FR / < 60%  
polyester FR**

ancho

**± 140 cm, ± 55 inches**

peso

**± 819 gr/m<sup>1</sup>, ± 26 oz/yd<sup>1</sup> fabrics**

combustión retardada

**EN 1021/ 1-2**

**BS 5852, crib 5**

**NF P 92 / 503 - 507, M1**

**DIN 4102, B1**

**UNI 9175, classe 1.IM**

**Cal TB 117**

**NFPA 260, class 1**

**IMO 2010 FTP part 8**

resistencia al desgaste

**ISO 12947-2**

100.000 rubs martindale

**ASTM D4157**

100.000 double rubs wyzenbeek

pilling

**ISO 12945-2**

4-5 (escala 1-5)

**ASTM D3511**

5 (escala 1-5)

resistencia al frotamiento

**ISO 105-X12**

mojado 4-5 / seco 4-5 (escala 1-5)

**AATCC 8**

mojado 4 / seco 4 (escala 1-5)

insensibilidad a la luz

**ISO 105-B02**

6 (escala 1-8)

**AATCC 16.3: 40 hours**

4.5 (escala 1-5)

resistencia al deslizamiento de costuras

**ISO 13936 - 2**

lizo 2 mm / trama 2 mm

**ASTM D4034**

lizo 89 lbs / trama 96 lbs

resistencia a la tensión

**ISO 13934-1**

warp 2500 N / weft 1550 N

**ASTM D5034**

warp 474 lbs / weft 262 lbs

mantenimiento



**carencia: lizo -2.6% / trama -1.9%**




STANDARD  
100

S07-0023  
Hohenstein HTTI

# dikson

7063.01 - 7063.14


---



7063.01




7063.02



7063.03




7063.04



7063.05



7063.06



7063.07




7063.08



7063.09



7063.10



7063.11



7063.12



7063.13



7063.14