

furka plus

7064.01 - 7064.44



binder

upholstery
vinyl

description

matt shimmer uni-coloured with fine grain

composition

vinyl coat on a cotton/polyester backing

width

± 137-140 cm, ± 54-55 inches

weight

backing: ± 110 gr/m², ± 5 oz/yd¹
coating: ± 690 gr/m², ± 31 oz/yd¹

thickness

1.1 mm, 0.04 inches

flame retardancy

EN 1021/1-2
BS 5852, crib 5
NF P 92/503 - 507, M2
NF D60-013 (AM 18)
DIN 4102, B2
UNI 9175, classe 1 IM
Cal TB 117
NFPA 260, class 1
IMO 2010 FTP part 8

abrasion

ISO 12947-2
> 300.000 rubs martindale
ASTM D4157
100.000 double rubs wyzenbeek

colorfastness to crocking

ISO 105-X12
wet 5 / dry 5 (scale 1-5)
AATCC 8
wet 5 / dry 5 (scale 1-5)

colorfastness to light

ISO 105-B02
7 (scale 1-8)
ASTM D4329: 150 hours
4 (scale 1-5)

resistance to blood, urine, sweat and sebum

EN 12720
5 (scale 1-5)

breaking strength

ISO 1421
length 470 N / width 313 N
ASTM D2261
length 7 lbs / width 9 lbs

flexibility

ISO 7854
400.000 cycles

adhesion to coating

ASTM D751
length 8 lbf / width 5 lbf



vinyl 
COMMITTED TO
SUSTAINABLE DEVELOPMENT

furka plus

7064.01 - 7064.44

