

# furka plus

7064.01 - 7064.44



binder

**upholstery**  
**vinyl**

omschrijving

**matglanzende uni met fijne nerf**

samenstelling

**geschuimde vinyl, katoen/polyester backing**

breedte

**± 137-140 cm, ± 54-55 inches**

gewicht

**backing: ± 110 gr/m<sup>2</sup>, ± 5 oz/yd<sup>1</sup>**  
**coating: ± 690 gr/m<sup>2</sup>, ± 31 oz/yd<sup>1</sup>**

dikte

**1.1 mm, 0.04 inches**

brandwerendheid

**EN 1021/1-2**  
**BS 5852, crib 5**  
**NF P 92/503 - 507, M2**  
**NF D60-013 (AM 18)**  
**DIN 4102, B2**  
**UNI 9175, classe 1 IM**  
**Cal TB 117**  
**NFPA 260, class 1**  
**IMO 2010 FTP part 8**

slijtvastheid

**ISO 12947-2**

> 300.000 rubs martindale

**ASTM D4157**

100.000 double rubs wyzenbeek

wrijftechtheid

**ISO 105-X12**

wet 5 / dry 5 (scale 1-5)

**AATCC 8**

wet 5 / dry 5 (scale 1-5)

lichtechtheid

**ISO 105-B02**

7 (scale 1-8)

**ASTM D4329: 150 hours**

4 (scale 1-5)

weerstand tegen bloed, urine, zweet en huidvet

**EN 12720**

5 (scale 1-5)

treksterkte

**ISO 1421**

length 470 N / width 313 N

**ASTM D2261**

length 7 lbs / width 9 lbs

knikbestendigheid

**ISO 7854**

400.000 cycles

hechting aan coating

**ASTM D751**

length 8 lbf / width 5 lbf



**vinyl**   
COMMITTED TO  
SUSTAINABLE DEVELOPMENT

# furka plus

7064.01 - 7064.44

---

